

Cibes Classic

Customized for your building

Our most popular product line of screw-driven platform home elevator has a self-supporting shaft enclosure made of panels in steel, aluminum or laminated safety glass with more than 240 color choices.



Indoor & Outdoor placement



Indoor & Outdoor placement

DESIGNED FOR FAST INSTALLATION & EASY USAGE

The smart prefabricated concept, attractive long-term cost of ownership and great choice of options make the platform lift the perfect home lift solution for most indoor and outdoor environments. All designed for fast installation and easy usage.

- ✓ Rated loads 300 , 400 , 500 kg
- ✓ Short installation time
- ✓ Power saving
- ✓ Low maintenance costs
- ✓ Screw and nut-driving mechanism
- ✓ Equipped with second motor in case of power outage

Classic Technical Overview

Rated load	300,400,500 kg
Rated Speed	0.15 m/sec 9 m/min
Travel height	20 m
Standard shaft finish	Steel panels RAL 9016
Shaft doors	Swing doors
Shaft door measurement	900 x 2000 mm
Half gate measurement	900 x 1100 mm
Driving system	Screw and nut, with safety nut
Control system	Micro computer based
Standard power supply	230/50/1, 16A(3x2.5mm ²) 400/50/3, 16A(5x2.5mm ²)
Motor power	2.2 / 4.0 kW
Optional	- Customized color - Aluminum shaft - Glass shaft - Folded seat - Passcode lock - Finger scan - RFID Tag
Manufactured in	Sweden



SIZE	PLATFORM (mm)		CUT OUT SIZE (mm)	
	LENGTH	WIDTH	LENGTH	WIDTH
XS	600	830	1020	980
S	800	830	1220	980
S	900	830	1320	980
S	1000	830	1420	980
S	800	930	1220	1080
S	900	930	1320	1080
S	1000	930	1420	1080
S	1100	930	1520	1080
M	800	1250	1220	1380
M	900	1250	1320	1380
M	1000	1300	1420	1430
M	1000	1400	1420	1530
L	1100	1400	1520	1530
L	900	1500	1320	1630
L	1000	1500	1420	1630
L	1100	1500	1520	1630
XL	1100	1600	1520	1760



Low energy consumption

Control panel

- Auto run
- Tactile & braille buttons
- Alarm button
- Emergency stop button
- LED-light
- Telephone



Premium forest floors and carpets



Premium lift colors